DOMINION SURE SEAL LTD. 6175 DANVILLE ROAD, MISSISSAUGA ONTARIO, CANADA L5T 2H7

## PRODUCT: SVG2 GRAVEL GUARD II SILVER/GREY 14.30Z/405G

CAS #..... NOT APPLICABLE







# Section 01: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURER DOMINION SURE SEAL LTD.
6175 DANVILLE ROAD, MISSISSAUGA
ONTARIO, CANADA L5T 2H7
PHONE: (905) 670-5411
CANUTEC EMBERGENCY #:1-613-996-6666(24HR)
SVG2 24005
PRODUCT NAME. GRAVEL GUARD II SILVER/GREY (VOC COMPLIANT)
CHEMICAL FAMILY. ORGANIC COATING.
MOLECULAR WEIGHT. MIXTURE.
CHEMICAL FORMULA. NOT APPLICABLE.
TRADE NAMES & SYNONYMS. NOT APPLICABLE.
PRODUCT USES. COATING.

Section 02: COMPOSITION/INFORMATION INGREDIENTS

| Occupi 62: Com Comonia Chimation inchediento |       |                |            |                               |                                   |
|--|-------|----------------|------------|-------------------------------|-----------------------------------|
| Hazardous Ingredients                        | %     | Exposure Limit | C.A.S.#    | LD/50, Route,Species          | LC/50 Route,Species               |
| ACETONE                                      | 15-40 | 750 ppm        | 67-64-1    | >9750 mg/kg ORAL - RAT        | >16,000 ppm (4 hr) INHAL -<br>RAT |
| TOLUENE                                      | 10-30 | 50 ppm         | 108-88-3   | 5000 mg/kg ORAL - RAT         | 8000 ppm (4 hr) INHAL -<br>RAT    |
| CALCIUM CARBONATE                            | 1-5   | 15 mg/m3       | 1317-65-3  | NOT AVAILABLE                 | NOT AVAILABLE                     |
| ORGANIC CLAY                                 | 1-5   | NOT AVAILABLE  | 68911-87-5 | NOT AVAILABLE                 | NOT AVAILABLE                     |
| ALUMINUM                                     | 1-5   | 10 mg/m3 ACGIH | 7429-90-5  | NOT AVAILABLE                 | NOT AVAILABLE                     |
| ISOBUTANE                                    | 5-10  | 1000 ppm       | 75-28-5    | NOT APPLICABLE                | 142,500 ppm (4h) INHAL -<br>RAT   |
| PROPANE                                      | 10-30 | 1000 ppm       | 74-98-6    | >5000 mg/kg<br>DERMAL-RABBITS | NOT AVAILABLE                     |

#### Section 03: HAZARDS IDENTIFICATION

#### Section 04: FIRST AID MEASURES

### Section 05: FIRE FIGHTING MEASURES

SENSITIVITY TO STATIC DISCHARGE....... NOT APPLICABLE. SENSITIVITY TO IMPACT....... NOT APPLICABLE.

| 00007682   | MATERIAL SAFETY DATA SHEET Page   |
|--|---|
| PRODUCT: SVG2 GRAVEL GUARD II S  | SILVER/GREY 14.3OZ/405G   |
| Section  | 05: FIRE FIGHTING MEASURES  |
| HAZARDOUS COMBUSTION PRODUCTS  | HYDROCARBON FUMES AND SMOKE. CARBON MONOXIDE WHERE COMBUSTION IS INCOMPLETE.  |
| AEROSOL FLAME PROJECTION CLASSIFIED AS: FLASHBACK  | >15cm BUT <100cm.   |
| Section 06:  | ACCIDENTAL RELEASE MEASURES   |
| LEAK/SPILL   | REMOVE ALL SOURCES OF IGNITION. USE AN INERT ABSORBENT MATERIAL, AND NON-SPARKING TOOLS. VENTILATE AREA. PREVENT FROM ENTERING A WATERCOURSE.   |
| Section  | 07: HANDLING AND STORAGE  |
| ENGINEERING CONTROLS   | KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAMES. VENTILATION - LOCAL (MECHANICAL IF USED INDOORS ON A CONTINUOUS BASIS). STORE IN A COOL, WELL VENTILATED AREA NOT TO EXCEED 50 DEG C. NONE KNOWN. |
| Section 08: EXPC   | OSURE CONTROLS/PERSONAL PROTECTION  |
| GLOVES/ TYPE   | IF USED INDOORS ON A CONTINUOUS BASIS, USE OF A CARTRIDGE TYPE RESPIRATOR (NIOSH/MSHATC 23C OR EQUIVALENT) IS RECOMMENDED. SAFETY GLASSES. NOT NORMALLY REQUIRED.                               |
| Section 09: P  | HYSICAL AND CHEMICAL PROPERTIES   |
| PHYSICAL STATE   | SILVER GREY.<br>AROMATIC ODOR.<br>NOT AVAILABLE.  |
| ĒVAPORATION RATEn-BUTYL ACETATE = 1 VAPOUR DENSITY (AIR=1)   |   |
| (BY WEIGHT). SOLUBILITY IN WATER g/L (20°C) pH SPECIFIC GRAVITY (LIQUID) COEFFICIENT OF WATER\OIL DIST | NOT APPLICABLE.<br>0.97-0.98.<br>NOT AVAILABLE.   |
| FREEZING POINT: (°C)   | 10: STABILITY AND REACTIVITY  |
| HAZARDOUS PRODUCTS OF  | HYDROCARBON FUMES AND SMOKE. CARBON MONOXIDE WHERE COMBUSTION IS  |
| CHEMICAL STABILITY:<br>YESNO, WHICH CONDITIONS?  | UNDER NORMAL CONDITIONS. NOT APPLICABLE   |
| COMPATIBILITY WITH OTHER SUBSTANCES: NO, WHICH ONES?REACTIVITY CONDITIONS?HAZARDOUS POLYMERIZATION     | STRONG OXIDIZING AGENTS. NOT APPLICABLE.  |
| Section 11   | : TOXICOLOGICAL INFORMATION   |
| IRRITANCY OF MATERIALSENSITIZING CAPABILITY OF MATERIALCARCINOGENICITY OF MATERIAL                     |   |

| 00007682  | MATERIAL SAFETY DATA SHEET Page   |  |  |  |
|---|---|--|--|--|
| PRODUCT: SVG2 GRAVEL GUARD II   | SILVER/GREY 14.3OZ/405G   |  |  |  |
| Section 1   | 2: ECOLOGICAL CONSIDERATIONS  |  |  |  |
| ENVIRONMENTAL   | NOT AVAILABLE.  |  |  |  |
| Section   | 13: DISPOSAL CONSIDERATIONS   |  |  |  |
| WASTE DISPOSAL  | DO NOT PUNCTURE OR INCINERATE CONTAINERS, EVEN WHEN EMPTY. DISPOSE OF IN ACCORDANCE WITH LOCAL, PROVINCIAL AND FEDERAL REGULATIONS.   |  |  |  |
| Section 1   | 14: TRANSPORTATION INFORMATION  |  |  |  |
| T.D.G. CLASSIFICATION   | . CONSUMER COMMODITY (AEROSOLS, UN1950, CLASS 2.1).<br>. CONSUMER COMMODITY, ORM-D.   |  |  |  |
| Section   | 15: REGULATORY INFORMATION  |  |  |  |
| CANADIAN REGULATIONS:   |   |  |  |  |
|   |   |  |  |  |
| U.S. REGULATIONS:   | ·   |  |  |  |
| HMIS RATING HEALTHHMIS RATING FLAMMABILITYHMIS RATING REACTIVITYHMIS RATING PERSONAL PROTECTIONNFPA CODE 30BSAPA 313 INFORMATION: | 4 SEVERE HAZARD.<br>0 MINIMAL HAZARD.<br>B.   |  |  |  |
|   | REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372:  CAS #: CHEMICAL NAME:  *108-88-3 TOLUENE  .*7429-90-5 ALUMINUM, POWDERED  THE FOLLOWING STATEMENT IS MADE IN ORDER TO COMPLY WITH THE CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986:  WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM. |  |  |  |
| TSCA (Toxic Substances Control Act)   | CAS #: CHEMICAL NAME: ALL COMPONENT OF THIS PRODUCT ARE LISTED ON THE TSCA INVENTORY. ANY   |  |  |  |
| V.O.C.(M.I.R.)<br>VOC (w/w%)  | IMPURITIES PRESENT IN THIS PRODUCT ARE EXEMPT FROM LISTING.  COMPLIES WITH CARB MIR = 1.20 FOR FLAT PAINTS.  LESS THAN 40.  |  |  |  |
| Sect  | tion 16: OTHER INFORMATION  |  |  |  |
| PREPARED BY   |   |  |  |  |